

What I claim as my invention is:

1. An apparatus for protecting the surface of a lally column comprising:
  - (a) a cover having a length and a width, the cover having two sides, a first side and a second side, the cover having two edges, a first edge and a second edge, the cover having a thickness of at least one-half (1/2) inch, the cover being fabricated from a dense foam material, whereby the cover would be wrapped around a lally column, and
  - (b) fastener means for removably attaching the first edge of the cover to the second edge of the cover once the cover has been wrapped around a lally column.
2. An apparatus according to claim 1 wherein the length of the cover would be approximately eight feet, and further wherein the width of the cover would be approximately eleven and one-half inches.
3. An apparatus according to claim 2 wherein the fastener means would further comprise:
  - (a) a strip of miniature hooks running lengthwise along the first edge on the first side of the cover for the entire length of the cover,
  - (b) a strip of miniature loops running lengthwise along the second edge on the second side of the cover for the entire length of the cover,

- (c) whereby a user would removably attach the strip of miniature hooks to the strip of miniature loops once the cover had been wrapped around a lally column.
4. An apparatus according to claim 2 wherein the fastener means would further comprise:
- (d) a first strip of tape running lengthwise along the first edge on the first side of the cover for the entire length of the cover,
- (e) a second strip of tape running lengthwise along the second edge on the second side of the cover for the entire length of the cover,
- (f) whereby a user would removably attach the first strip of tape to the second strip of tape once the cover had been wrapped around a lally column
5. An apparatus for providing safety and for individuals and external objects comprising:
- (a) a cover having a length and a width, the cover having two sides, a first side and a second side, the cover having two edges, a first edge and a second edge, the cover having a thickness of at least one-half (1/2) inch, the cover being fabricated from a dense foam material, whereby the cover would be wrapped around a lally column, and
- (b) fastener means for removably attaching the first edge of the cover to the second edge of the cover once the cover has been wrapped around a lally column.

6. An apparatus according to claim 5 wherein the length of the cover would be approximately eight feet, and further wherein the width of the cover would be approximately eleven and one-half inches.
7. An apparatus according to claim 6 wherein the fastener means would further comprise:
- (g) a strip of miniature hooks running lengthwise along the first edge on the first side of the cover for the entire length of the cover,
  - (h) a strip of miniature loops running lengthwise along the second edge on the second side of the cover for the entire length of the cover,
  - (i) whereby a user would removably attach the strip of miniature hooks to the strip of miniature loops once the cover had been wrapped around a lally column.
8. An apparatus according to claim 6 wherein the fastener means would further comprise:
- (a) a first strip of tape running lengthwise along the first edge on the first side of the cover for the entire length of the cover,
  - (b) a second strip of tape running lengthwise along the second edge on the second side of the cover for the entire length of the cover,
  - (c) whereby a user would removably attach the first strip of tape to the second strip of tape once the cover had been wrapped around a lally column.